

	GTV 300 Vie Della Moda	LXV 125 LXV 125 Vie Della Moda	GTS 300 GTS 300 Touring	LX 125 3V LX 125 3V Touring
<i>Engine</i>	QUASAR 4-stroke 4 valve single cylinder, electronic injection, catalysed	LEADER 4-stroke single cylinder, with catalytic converter and electronic injection	QUASAR 4-stroke 4 valve single cylinder, electronic injection, catalysed	4-stroke single cylinder, with catalytic converter and electronic injection
<i>Engine capacity</i>	278 cc	124 cc	278 cc	124 cc
<i>Bore x Stroke</i>	75 mm x 63 mm	57 mm x 48.6 mm	75 mm x 63 mm	52 mm x 58.6 mm
<i>Max. power at crankshaft</i>	15.8 kW -21.5 hp- at 7500 rpm	7.9 kW -10.7 hp- at 8250 rpm	15.8 kW -21.5 hp- at 7500 rpm	8.5 kW -11.6 hp- at 8250 rpm
<i>Max. torque</i>	22.3 Nm at 5000 rpm	9.6 Nm at 6500 rpm	22.3 Nm at 5000 rpm	10.7 Nm at 6500 rpm
<i>Fuel system</i>	PI injection - (Port Injected)	PI injection - (Port Injected)	PI injection - (Port Injected)	Port Injected
<i>Cooling</i>	Liquid	Forced air	Liquid	Forced air
<i>Starter</i>	Electric	Electric	Electric	Electric with freewheel
<i>Transmission</i>	CVT with torque server			
<i>Clutch</i>	Automatic dry centrifugal clutch with vibration dampers			
<i>Load bearing structure</i>	Sheet metal body with welded reinforcements			
<i>Front suspension</i>	Single link arm with coil spring and dual action hydraulic shock absorber			
<i>Rear suspension</i>	Coil springs with adjustable preload (4 positions) and two dual action shock absorbers	Coil springs with adjustable preload (4 positions) and two dual action shock absorbers	Coil springs with adjustable preload (4 positions) and two dual action shock absorbers	Coil springs with adjustable preload (4 positions) and two dual action shock absorbers
<i>Front brake</i>	Hydraulically operated 220 mm stainless steel disc	Hydraulically operated 200 mm stainless steel disc	Hydraulically operated 220 mm stainless steel disc	Hydraulically operated 200 mm stainless steel disc
<i>Rear brake</i>	Hydraulically operated 220 mm stainless steel disc	110 mm drum mechanically operated	Hydraulically operated 220 mm stainless steel disc	Mechanically operated 110 mm Ø drum
<i>Front tyre</i>	Tubeless 120/70 - 12"	Tubeless 110/70 - 11"	Tubeless 120/70 - 12"	Tubeless 110/70 - 11"
<i>Rear tyre</i>	Tubeless 130/70 - 12"	Tubeless 120/70 - 10"	Tubeless 130/70 - 12"	Tubeless 120/70 - 10"
<i>Length / Width / Wheelbase</i>	1930 / 770 / 1370 mm	1770 / 740 / 1280 mm	1930 / 755 / 1370 mm	1770 / 740 / 1280 mm
<i>Seat height</i>	790 mm	785 mm	790 mm	785 mm
<i>Fuel tank capacity</i>	9.5 litres	8.2 litres	9.2 litres	8.2 litres
<i>Emissions compliance</i>	Euro 3	Euro 3	Euro 3	Euro 3

*[data for these versions in brackets when different]

Colours and specifications are correct at the time of publishing (April 2013). Vespa reserves the right to change colours and specifications at any time without notice. Always check specification and availability with your local Vespa dealer when you order. Pictures are for illustration purposes only, actual colours may vary. Errors and Omissions Excepted.

For prices and to locate your nearest dealer call Freephone 0844 967 1849 or visit www.uk.vespa.com

GTS 300 (125 ie)* Super
GTS 300 (125 ie)* Super Sport

LX 50 2T
LX 50 2T Touring

PX 150 (125)*

QUASAR 4-stroke 4 valve single cylinder, electronic injection, catalysed	Hi-PER2 2-stroke with catalytic converter	2-stroke single cylinder, with catalytic converter
278 cc (124 cc)	49 cc	150 cc (123 cc)
75 mm x 63 mm (57 mm x 48.6 mm)	40 mm x 39.3 mm	57.8 mm x 57 mm (52.5 mm x 57 mm)
15.8 kW -21.5 hp- at 7500 rpm (11 kW -15 hp- at 9750 rpm)	-	5.8 kW -7.9 hp- at 6000 rpm (5 kW -6.8 hp- at 6000 rpm)
22.3 Nm at 5000 rpm (12 Nm at 7500 rpm)	-	11.2 Nm at 4000 rpm (9.9 Nm at 4250 rpm)
PI injection - (Port Injected)	Carburettor	Carburettor
Liquid	Forced air	Forced air
Electric	Electric and kick starter	Electric and kick starter
CVT with torque server		Manual, 4-speed
Automatic dry centrifugal clutch with vibration dampers		Multiplate wet clutch
Sheet metal body with welded reinforcements		Sheet steel body
Single link arm with coil spring and dual action hydraulic shock absorber		
Coil springs with adjustable preload (4 positions) and two dual action shock absorbers	Coil spring with dual action hydraulic shock absorber	Coil spring with dual action hydraulic shock absorber
Hydraulically operated 220 mm stainless steel disc	Hydraulically operated 200 mm stainless steel disc	Hydraulically operated 200 mm stainless steel disc
Hydraulically operated 220 mm stainless steel disc	Mechanically operated 110 mm Ø drum	Mechanically operated 150 mm Ø drum
Tubeless 120/70 - 12"	Tubeless 110/70 - 11"	Tubeless 3.50 - 10"
Tubeless 130/70 - 12"	Tubeless 120/70 - 10"	Tubeless 3.50 - 10"
1930 / 755 / 1370 mm	1755 / 740 / 1280 mm	1780 / 745 / 1250 mm
790 mm	775 mm	805 mm
9.2 litres	8.5 litres	8 litres
Euro 3	Euro 2	Euro 3



Twelve months roadside recovery on all scooters over 50cc



All inclusive customer finance: contact your dealer for details





Contact your Piaggio dealer or call 0845 601 3095 for an insurance quote



All scooters come with a 2 year warranty



The Trademark  is the property of  PIAGGIO & C.s.p.a.